

Version: 9714R2
Release date: 2025-03-12

ADDED

- New NIBE logo at startup

CHANGES

- Fixed issue with reset of alarms from myUplink
- Fixed issue with some units losing contact with myUplink
- Fixed an issue that could cause communication errors with, for example, a slave heat pump
- Fixed issue where the counter for the energy meter could reset to zero
- Updated functionality towards myUplink
- Minor adjustments to menu and menu texts

Version: 9699R7
Release date: 2024-09-30

- New Nord pool / Epex Spot zones for Smart Price Adaption (GER, DE-LU, PL, FR, AT)
- The TSS20 accessory is now supported

CHANGES

- Fixed issue with menu 4.1 not visible on myUplink even when SPA is available
- Fixed issue with room setpoint and parallel offset not visible on tile
- Updated functionality against myUplink

Version: 9699R5
Release date: 2024-07-02

CHANGES

- Fixed issue with the unit not connecting to myUplink after update

Version: 9699R4
Release date: 2024-06-03

ADDED

- AUX output with flow protection cooling indication. Possible to select NO or NC
- AUX input, "Flow guard brine"
- AUX input to allow heating/cooling even if operation mode not allow it
- Hot water out (BT70) and Hot water circulation (BT82) sensors for Hot water circulation systems on AUX-in
- New text translations
- Support for Portuguese language
- Pump exercise on GP10

CHANGES

- Connects to myUplink instead of NIBE Uplink. Connected systems are migrated. The owner needs to register an myUplink account with the email address used for their previous NIBE Uplink account to gain access to updated online service
- Changed default DOT temperature for Netherland and Belgium to -10 degrees
- Smart price Adaptation: Updated function for better handling of negative electricity prices
- Fixed alarm handling of BT5/BT7 sensor alarms when sensors are attached to AUX input
- Fixed internal addition being blocked if 0.0kW is selected in menu 5.1.12
- Minor adjustment of menu and menu texts

Version: 9443R7
Release date: 2023-01-16

ADDED

- Is it now possible to select "UPM4 25–75 130" as heating medium pump in menu 7.4

Version: 9443R6
Release date: 2022-12-05

ADDED

- PC model only: It is now possible to deactivate the PC function

Version: 9443R5
Release date: 2022-03-22

CHANGES

- Improved control of the PVT-source / AAC accessory

Version: 9443R3
Release date: 2021-07-09

ADDED

- It is now possible to select Charging method "target temp" for hot water charging with several compressors
- Support for new display hardware.

CHANGES

- Updated texts and translations
- Refined control of Brine pump for multi-operation
- Fixed an issue with heating medium pump control in active cooling
- EME alarm 504 (The inverter has a message) changed from red light alarm to info alarm. Does no longer appear in the alarm log
- When a demand for POOL 2 stops, a "Top up" of hotwater i performed.
- ECS shunts now close during hot water charging and pool to prevent water from circulating backwards in climate system 1, Does not apply if sensor BT25 is installed
- Default is now 7 days for time between periodic increase of hot water
- Fixed an issue where NV10 alarms did not block slaves in multi-operation
- Fixed an issue where Alarm 371 "low groundwater temperature" did not block slaves in multi-operation
- The serial number of products manufactured on day 366 (leap year) is now accepted by the software

Version: 9240R3
Release date: 2020-11-11

ADDED

- Popup menu is now requesting a restart of the machine if selected protocol is changed in menu 5.2.1

CHANGES

- Improved control of ground water pump
- Improved control of brine pump in passive cooling
- Improved control of heating medium pump (GP1).

Version: 9240R2
Release date: 2020-03-05

ADDED

- Possibility to be docked as a slave to a S-series product

CHANGES

- Supports the accessory NIBE PVT 40
- Solves a problem with cooling DM together with HPAC
- Detecting of phase order is removed in 3x230V models
- Minor adjustments of menus and texts
- Solves a problem that flow values was shown even though flow meter BF1 was not connected
- Improved control of heating medium pump GP1
- Improved control of brine pump GP2
- Power at DOT in menu 5.1.26 can be set up to 1000kW

Version: 9172R2
Release date: 2019-04-18

ADDED

- EME20: It is now possible to choose "priority household electricity" in menu 4.1.11 (Solar electricity) if external energy meter is connected.
- Is now possible to choose "heat medium return (BT71)" on AUX-in (Menu 5.4)
- Now supports Master/slave function.
- Alarm for pressure switch climate system added. Activates through AUX-input. Alarm number 165 "Low pressure climate system". The alarm is a redlight alarm without control action but lights the red diode and can give a notification through Uplink or SMS.
- Added a solution to problems scrolling in the menus. Prevents the display pointer from going back and forth. This eliminates the need to replace the display unit due to this problem.
- Added possibility to set minimum allowed speed in heating for heating medium pump
- New setting in menu 5.1.9 (brine pump speed), "Speed extern. contr (AUX)" by activating brine pump on AUX-in.
- Now supports the accessory external energy meter Address
- Extra climate system 2 - 8: It is now possible to block the shunt on AA5-X2:13-14. When there is a connection the shunt closes.

CHANGES

- Minor adjustments of menus and texts
- EME20: Improved communication with the accessory.
- Improved control of heating medium pump GP1 and brine pump GP2
- ACS (active/passive cooling): Improved control
- Improved display of "my icons". Prevents that part of the outdoor temperature is hidden when the aluminium door is closed.
- Solved incorrect names on climate system 2-8 in service info
- Improved compressor regulation
- Improved control of the accessory HTS
- EME10: In the automatic search of accessories, EME10 could incorrectly be activated even though it was not installed

Version: 8539R4

Release date: 2019-01-17

ADDED

- Solves a problem in the 6kW model that could, under special circumstances, cause the hot water production to fail

Version: 8539R3

Release date: 2018-04-10

ADDED

- Now supports 4 units of the accessory ERS.
- Country selection Australia and New Zealand added
- Stove guard function added for ERS
- Now supports 4 units of the accessory HTS.
- It is now possible to choose night cooling, separately for each FLM in menu 5.3.1

CHANGES

- EME20: Management of alarm update
- Time zone Istanbul is now corrected and is always delayed with 3h compared to UTC*Updated circulation pump regulation
- Improved compressor regulation
- AXC40: Now possible to control shunt control addition with 0-10V signal
- Improved control of ground water pump
- EME10 is now regulated on power instead of current. New setting in menu 4.1.10 which indicates if EME10 is on single or three phase
- EME20 now supports up to 12 PV-inverters
- Min supply for the accessory HPAC can now be set down to -5, earlier +5 grader in menu 1.9.3.2
- Load monitor: Solved a problem with the alarm 182 could indicate when a new internal electric step were going to step in
- Improved control of the accessory HPAC at operation mode active cooling and run priority is hot water or pool
- Solves a problem that could make the product to restart if the activated vacation period was longer than 127 days
- Improved control of accessory ERS

Version: 8218R4

Release date: 2017-12-06

CHANGES

- Improved integration with Smart Price Adaption toward NIBE Uplink API.
- Improved control of the brine pump in active cooling at dockning towards the accessory HPAC.
- Solved a problem with displayed measured flow with the accessory EMK in Uplink. Previously measured value could be lost at low flows.
- Removed a term for country selection Belgium: Max internal addition was 1kW.

Version: 8218R3

Release date: 2017-10-11

CHANGES

- Solved a problem with languages; Icelandic and Turkish was missing in menu 4.6.

Version: 8218R2
Release date: 2017-08-31

ADDED

- Supports the accessory EME20
- "Activate economy" can now be selected on the AUX-in (Menu 5.4)
- "Smart control" can now be selected in menu 2.2
- Smart Price Adaption is now supported if country selection Norway

CHANGES

- Improved control of the brine pump
- Improved control of Smart home function
- MODBUS40: Improved control of 32-bites register
- AXC40: It is now possible to control the ground water pump with 0-10V signal
- Solves a problem that caused the accessory shunt control brine in menu 5.2 to deactivate if a restart occurred
- Smaller adjustments of menus and menu texts

Version: 7998R3
Release date: 2017-05-24

ADDED

- "Åland" is added in the country selection menu
- ERS: Possible to choose bypass function without BT50 and blocked heat
- Soft output (AUX) now also shows status in the service info 3.1, it used to only show function
- SMS40 now also sends SMS when a filter alarm occurs
- It is now possible to choose the amount of pulses/kWh or energy/puls for external energy meter in menu 5.3.
- AXC40: Possible to regulate step control addition with 0-10V signal

CHANGES

- It is now possible to choose fuse size up to 400A
- Smaller adjustments of menus and menu texts.
- Improved automatic resetting of the alarm "low KB" with HPAC accessory
- Information message "inverter fault" it now termed as "protection mode inverter"
- Improved compressor regulation

Version: 7740R5
Release date: 2017-01-12

ADDED

- Improved function for the accessory EMK.

CHANGES

- 12 och 16kW models: Improved tolerance in case of under- and over voltage
- 12kW 3x400V, export models: Solves a problem that made the connection of the first electric step fail to activate

Version: 7740R4
Release date: 2016-11-03

ADDED

- Vacation can now be set in AUX-out (menu 5,4)
- Icelandic language added
- Now support accessory SES and OPT
- In F1155* it is now possible to choose hotwater charge method "target temp" in menu 5.1.1

CHANGES

- Solves a problem that could cause inverter alarm 216
- Improved routine for stopping the compressor when closing down by the switch (SF1)
- Minor bugfixes and improvements
- Auto settings; start addition is now default 5 degrees
- Minor adjustments of menus and texts
- Improved network stability
- Improved solar cooling function on Solar 40
- If country selection Belgium; the effect is now limited to 1 electrical step. (0.5kW/1 kW/1.33kW depending on the immersion heater)

Version: 7312R9
Release date: 2016-09-30

ADDED

- Support added for new type of memory circuit for the display unit. This update affects only upcoming displays with changed hardware.

Version: 7312R8
Release date: 2016-06-22

ADDED

- Support for accessory ERS

CHANGES

- Improved function of step controlled addition (AXC 40)

Version: 7312R6
Release date: 2016-05-20

ADDED

- Smart price adaption is now supported with country selection Estonia

CHANGES

- Improved function with accessory EME 10.
- Minor bugfixes and improvements

Version: 7312R4
Release date: 2016-04-11

CHANGES

- Improved compressor heating function for 6kW and 12kW.
- Improved compressor control
- Improved circulation pump control
- It is now possible in PC models to choose "dt-cooling" at passive cooling in menu 5.1.9
- Other minor bug fixes and improvements